

FEATURES

- Open access under primary filters
- Automatic, continuous self-clean filters
- 2 Stage MERV 14 filtration
- High efficiency fans for quiet operation
- Powder coated upper plenums
- Fits flat to building wall
- Filter monitoring gauges
- Optional Fluidized collection hoppers
- Shipped pre-assembled and factory tested
- Standard widths: 6ft. 9ft. 12ft.
- Working enclosures – Galvanized or S.S.



SERVAIR Batch Powder Booth (SPB) Specifications

SPECIFICATIONS	6000	8000	10000	12000
Dimensions W x H x D	6ft. X 10ft. 9in. X 3ft.	9ft. X 10ft. 9in. X 3ft.	12ft. X 10ft. 9in. X 3ft.	12ft. X 10ft. 9in. X 3ft.
Airflow (CFM)	6000	8000	10000	12000
Primary Filters Length (Qty.)	48in. (4)	48in. (6)	48in. (8)	48in. (8)
Final Filters Dimensions (Qty.)	21in. x 36in. x 6in. (2)	24in. x 36in. x 12in. (3)	24in. x 36in. x 12in. (4)	24in. x 36in. x 12in. (4)
MOTOR				
HP	5	10	10	15
RPM	1750	1750	1750	1750
208V / 60Hz (Amps)	14.9	30.3	30.3	41
230V / 60Hz (Amps)	13	26.3	26.3	35.6
460V / 60Hz (Amps)	6.5	13.2	13.2	17.8
575V / 60Hz (Amps)	5.2	11.4	11.4	14.5
Controls (1-Phase)	110/60/10	110/60/10	110/60/10	110/60/10

Optional Components

- Powder Collection Hopper/Ramp
- Class I Div II Light Fixtures
- Cartridge Baffle
- Custom Enclosures
- Floor deflector plate
- Variable Frequency Drive